ENGLISHMAN'S BAY



ENGLISHMAN'S BAY

STONE INFORMATION:

| Quarry Location: | Jonesboro, Maine | | | |
|--------------------------------|---|-------------------------|--------------------------------|-----------------|
| Available In: | Blocks, Slabs, Cut to Size | | | |
| Popular Applications: | Architectural and Landscaping Stone, Building Cladding, Monuments, Countertops, Benches, Chimneys, Curbing, Steps, Paving Stone | | | |
| Technical Information: | | | The last of the | North Mark |
| | Eng | glish | Metric | Test Method |
| Absorption by weight | .3 | 3% | .33% | ASTM C97-47 |
| Density (Specific gravity) | 168 lbs, | /ft ³ (2.62) | 2,686 kg/m ³ (2.62) | ASTM C97-47 |
| Compression strength | 23,6 | 55 psi | 163.1 MPa | ASTM C170-50/90 |
| Modulus of rupture | 2,21 | 2 psi | 15.3 MPa | ASTM C99-52 |
| | 57 | 5 HA | n/a | ASTM C241-51 |
| Abrasion resistance (hardness) | 57. | 51111 | | |

CONTACT INFORMATION:

Stone Center : 545 Rockland Rd (Rt.17) Jefferson, Maine 04348

Mailing Address: P.O. Box 177 Washington, ME 04574

Phone: (207) 549-4729

Fax: (207) 549-4032

Website: www.jcstoneinc.com



DISCLAIMER:

Stone is a natural product and will vary in color. Due to printing processes, the images published herein are intended for reference purposes only. In circumstances where color matching is critical, please contact us for a physical stone sample.